### (19) World Intellectual Property Organization International Bureau





#### (43) International Publication Date 1 August 2002 (01.08.2002)

### (10) International Publication Number WO 02/058504 A1

HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,

(51) International Patent Classification7:

(21) International Application Number: PCT/IB01/00109

(22) International Filing Date: 26 January 2001 (26.01.2001)

(25) Filing Language:

English

A45D 8/20

(26) Publication Language:

English

(72) Inventor: RIZZUTO, Leandro, P. [US/US]; 229 Byram Shore Road, Greenwich, CT 06830 (US).

(71) Applicant and

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,

LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

#### Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HAIR ORNAMENT WITH A RESILIENT ATTACHING CLIP



(57) Abstract: Hair ornament with a resilient attaching clip comprising a pair of complementary transversally clongated limbs (12, 14) having handle portions (30, 32) and which are connected by hinge and spring means (16) and having suitably shaped prongs (18) extending from each elongated limbs (12, 14) and forming a pair of clipping portions wherein each elongated limb comprises a socket (20, 22) having a hollow cylindrical recess and which forms at the inner opposite end abutting sliding planes (23, 25), as well as a bushing (24) which is received in a recess provided in the respective socket of each limb, whereby the limbs are pivoted to each other and a spring (26) inserted in the bushing extending into the sockets and being attached at both ends by suitable means at the outer end of the sockets in order to bias the limbs in the closed position.

WO 02/058504 PCT/IB01/00109

1

5

# HAIR ORNAMENT WITH A RESILIENT ATTACHING CLIP

10

# FIELD OF THE PRESENT INVENTION

[0001] The invention relates to a hair ornament and particularly to a device having an esthetical aspect, i.e. a highly ornamental appearance and comprising novel means combined therewith for attaching it to the hair of the wearer.

[0002] An important object of the invention is to provide such a device wherein the means for attaching the device to the hair is in the form of a clip positioned by a 20 hinge and spring means which remain wholly hidden from view when the ornament is borne in the hair, and which can be firmly clamped in the hair.

### BACKGROUND AND PRIOR ART OF THE PRESENT INVENTION

25 [0003] Devices intended to be used as an ornament and comprising a resilient attaching clip have been widely used.

[0004] They comprise a spring mean intended to clip two parts or limbs connected by a hinge for securing the 30 device to the hair of the wearer.

[0005] Such hinge and sometimes the spring are externally visible and sometimes hair remains entangled with the hinge mechanism.

[0006] Obviously, the visibility of the hinge and

#### **CONFIRMATION COPY**

2

WO 02/058504 PCT/IB01/00109

spring and, of course, the possibility of entaglement with the hair are undesirable features, which the device of the invention seeks to avoid.

[0007] Other objects and advantages of the invention will become apparent during the course of the following description.

# BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Figure 1 is an exploded view of the main

10 parts of the device according to the invention ;

[0009] Figure 2 is a side perspective view of the device in closed position;

[0010] Figure 3 is a further perspective face view of the device in open position.

15 [0011] Figure 4 is a view corresponding to Figure 2 but in an open position;

[0012] In the drawings, the same numerals are used for identical parts for all the Figures.

### 20 DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

[0013] Referring to the drawings, the numeral 10 designates the body of the device shown in the present instance as comprising a pair of complementary transversally elongated limbs 12 and 14, which are connected by hinge and spring means 16 and having suitably shaped prongs 18 extending from each elongated limbs 12 and 14. The prongs 18 form a pair of clipping portions or jaws allowing, when they are in the closed position, to maintain the device in the hair of the bearer.

30 [0014] Each elongated limb 12 and 14 comprises a socket 20 and 22 (represented as substantially cylindrical shaped), having a hollow cylindrical recess which is preferably closed at the outer end thereof and which forms at the inner opposite end to the outer end, abutting

WO 02/058504

30

3

sliding planes 23 and 25 which, as represented, are inclined at an angle of 45° approximately in respect of the common axis X-X' of the elongated sockets 20 and 22.

[0015] The socket 20, as represented for one limb 12 extends over one half of the length of said limb and the socket 22 for the second limb 14 also extends over one half of the length of the corresponding limb.

[0016] A bushing 24 may be received in the recesses of the sockets 20 and 22 and a spring 26 may be in turn located in the bushing 24.

[0017] The limbs 12 and 14 are thus pivoted to each other by means of said bushing 24. Furthermore, the spring 26 located in the bushing 24 extends into the sockets 20 and 22 and is attached at both ends by suitable means, such 15 as the pins or plugs 34 at the outer end of the sockets 20 and 22 so as to bias the limbs 12 and 14 in the closed position.

[0018] The spring 26, as shown at both ends comprises hook parts allowing the mounting of the device in the closed position with the pins 34 securing the spring in a permanent traction bias to clip into the hair. When the lugs 30, 32 are pressed, the rotation of the limbs 12 and 14 will cause the stretching out (extension) of these limbs causing the elongation of the spring. When these lugs are no longer pressed, the limbs revert to the closing (gripping) position.

[0019] Handle portions 30 and 32 in the form of lugs allow to open the device starting from an abutment position (such as represented in Fig. 2) to an open position (as in Fig. 3 and 4).

[0020] Although in Figure 1, the bushing is represented as a separate part, said bushing could be solid with e.g. the socket 20, i.e. be part of the socket but having an outer smaller diameter in order to allow it to be

WO 02/058504 PCT/IB01/00109

received into the socket 22.

[0025]

[0021] In Fig. 2, the contact of the prongs 18 of each limb 12 and 14 causes the abutment position.

[0022] The prongs 18 could however be offset for the first limb 12 compared to the prongs 18 for the second limb 14 and abutment parts may then be provided at suitable positions on the limbs proper in the closed position.

[0023] The sliding planes 23, 25 will cause the limbs 12 and 14 when the lugs 30, 32 are pressed by the 10 fingers of the user against the biasing due to the spring 26 to move from the position of Fig. 2 toward the position of Fig. 3 and 4 but also to "stretch out" the limb 12 of the device from the limb 14, thus extending the spring 26.

[0024] As soon as the pressing action is released,
15 under the action of the spring 26, a sliding of the two
inclined planes 23, 25 of the sockets 20 and 22 will cause
the device to revert to its initial closed position.

device, the two sliding planes appear as an inclined line,

thus forming a hidden hinge in all the positions of the
device (open or closed). Furthermore, the spring 26 also
remains hidden from the view, be it for the outside or the

As seen from the outside (rear) of the

inside, only the bushing 24 being visible from the inside.

[0026] The number of prongs and their position as

25 well as their shape can of course be adapted to the intended specific use and are not necessarily as shown on the drawings.

[0027] The device of the invention can be made of metal or plastic.

The finger grasping portion (i.e. the lugs 30, 32) can also have various dimensions and sizes, provided they can be used properly as handles.

[0028] It should be noted that the spring 26 may also be fixed by the pins 34, in the closed position of the

5


device not only as being biased under traction but also as being twisted in such a manner that the opening movement under the pressure on the lugs 30 and 32 will cause it to be twisted even more. In such case the planes 23 and 25 may have an inclination different from what is shown and may even be perpendicular to the said axis X-X'.

[0029] It is to be understood that the form of the invention shown and described is to be taken as a preferred example of the same and that various changes in the shape,

10 size and arrangement of the parts may be made, without departing from the scope of the claims.

#### CLAIMS

- 1. Hair ornament with a resilient attaching clip comprising a pair of complementary transversally elongated limbs having handle portions and which are connected by hinge and spring means and having suitably shaped prongs extending from each elongated limbs and forming a pair of clipping portions wherein each elongated limb comprises a socket having a hollow cylindrical recess and which forms at the inner opposite end abutting sliding planes, as well as a bushing which is received in a recess provided in the respective socket of each limb, whereby the limbs are pivoted to each other, and a spring inserted in the bushing, extending into the sockets and being attached at both ends by suitable means at the outer end of the sockets in order to bias the limbs in the closed position.
- Hair ornament according to claim 1, wherein the said sliding planes are inclined at an angle of approximately 45° in respect of a common axis of the said sockets, in order to cause the stretching out of the limbs
   and the elongation of the spring against its bias, when the handle portions are pressed.
  - 3. Hair ornament according to claim 1, wherein the said prongs are in an abutment position when the hair ornament is in the closed position.
- 4. Hair ornament according to claim 1, wherein the said prongs are offset for the first limb compared to the prongs for the second limb, parts provided on the limbs abutting each other in the closed position.



Ir I Application No PCT/IB 01/00109

	· · · · · · · · · · · · · · · · · · ·								
A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A45D8/20									
According to International Patent Classification (IPC) or to both national classification and IPC									
B. FIELDS SEARCHED									
Minimum documentation searched (classification system followed by classification symbols)									
IPC 7 A45D									
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched									
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)									
EPO-Internal									
	,								
C. DOCUMENTS CONSIDERED TO BE RELEVANT									
Category °	Citation of document, with indication, where appropriate, of the rel	evant passages ·	Relevant to claim No.						
А	US 5 494 060 A (POTUT CHRISTIAN)		1-4						
	27 February 1996 (1996-02-27)								
	the whole document								
A	US 6 082 371 A (BADER-SALTZMAN GERALDINE 1-4								
	ROSE ET AL) 4 July 2000 (2000-07-04)								
	the whole document								
	·	,							
Further documents are listed in the continuation of box C.    X   Patent family members are listed in annex.									
Special categories of cited documents:									
*A* document defining the general state of the lart which is not clied to understand the principle or theory underlying the									
*E' earlier document but published on or after the international "X" document of particular relevance; the claimed invention									
*L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another  "V* document which may throw doubts on priority claim(s) or involve an inventive step when the document is taken alone  "V* document of naticular solutions the along the solutions of the solution o									
"V" document of particular relevance; the claimed invention called or shorter special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or other special reason (as specified)  "O" document referring to an oral disclosure, use, exhibition or									
other means ments, such combination being obvious to a person skilled									
later than the priority date claimed "&" document member of the same patent family									
Date of the actual completion of the international search  Date of malling of the International search report									
2	5 October 2001	05/11/2001							
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2		Authorized officer							
	NL – 2280 HV Rijswijk Tel. (+31–70) 340–2040, Tx. 31 651 epo ni,	1							
	Fax: (+31-70) 340-3016	Lang, D							

Form PCT/ISA/210 (second sheet) (July 1992)

# INTERNATIONAL SEARCH REPORT

In al Application No

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5494060	Α .	27-02-1996	FR DE EP US	2716609 A1 69501409 D1 0669088 A1 5664591 A	01-09-1995 19-02-1998 30-08-1995 09-09-1997
US 6082371	. A	04-07-2000	NONE		

Form PCT/ISA/210 (patent family annex) (July 1992)